

Premium Linear Highbay Plus Motion Sensor

Product of The Year!



**ZENERGY**
The LED Revolution

Premium Highbay

The IKIO Premium High Bay Series is designed for a wide variety of applications and mounting heights. Wide angle optics, multiple lumen packages and color temperatures make these ideal for industrial, commercial, manufacturing, gymnasium and other applications, that utilize traditional linear fluorescent and HID High Bay. Suggested mounting heights are between 15 - 25 feet. This High Bay reduces up to 70% energy, and has a life span of over 10 years. This fixture comes with frosted or clear lens as an option.

Features

- Aluminum heat sink for optimum heat dissipation
- Average efficacy of 130+ Lm/W
- Matte white paint with an option of frosted or clear lens provide pleasing architectural aesthetics with non-glare reflective surfaces
- 100,000 hour rated lifetime at L70
- 80+ CRI
- 0-10v dimming(optional)
- 10-Year Manufacturer's Warranty
- LM79/LM80/TM-21 data available (on request)

800-931-5662 . Sales@ZnergyWorld.com

Product of The Year
Most Innovative Product
200 Lumens Per Watt
LED Expo

Powered by
**IKIO**
LED LIGHTING



Product Code	IK-HBPS-L200-XXXX-XX XXX				
Size (ft)	1.89 x 0.80	3.58 x 0.80	1.89 x 1.55	3.58 x 1.17	3.58 x 1.55
Power Consumption (W)	50	110	150	220	300
Lumen Output (Lm)	10000 ± 5%	22000 ± 5%	30000 ± 5%	44000 ± 5%	60000 ± 5%
Lumen Efficacy (Lm/w)	200 ± 5%				
CCT (K)	4000 ± 5%		5000 ± 5%		
Color Rendering Index (CRI)	80+				
AC Input Rating (VAC)	AC 100-277 v 50/60Hz				
Dimming (0-10v)	Optional				
PF	≥ 0.90				
Certifications					


ORDERING INFORMATION

MODEL	LUMEN EFFICACY	POWER	CCT
IK-HBPS	L200	0050	40
		0 - 050 W	40 - 4000 K
		0 - 110 W	50 - 5000 K
		0 - 150 W	
		0 - 220 W	
		0 - 300 W	

OPTOMETRIC DATA


IK-HBPS-L200-0050-XX XXX

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



IK-HBPS-L200-0100-XX XXX

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



IK-HBPS-L200-0200-XX XXX

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

