Magnetic Strip 4'





The IKIO Magnetic Strip Series is economy-level LED retrofit for 1'X4', and 2'x4' recessed and surface mounted troffers in existing drop-in ceilings. These kits are easy to install, using simple hand tools with minimum modification to the existing housing.

Features

Average efficacy of 110+ Lm/W
Wide aluminum carrier angles for added heat sinking and optic diffusion
100,000 Hour rated life at L70
80+ CRI
0-10v dimming(optional)
10-Year Manufacturer's Warranty
LM79/LM80/TM-21 data available (on request)















TECHNICAL SPECIFICATIONS

Product Code	IK-MT24-L110-XXX-XX XXX									
Strip	2	3	4	2 3		4	2 3		4	
Power Consumption (W)	10			15			20			
Lumen Output (Lm)	2200±5%	3300±5%	4400±5%	3300±5%	4950±5%	6600±5%	4400±5%	6600±5%	8800±5%	
Lumen Efficacy (Lm/w)	110±5%									
CCT (K)	3000±5% 4000±5% 5000±5%									
Color Rendering Index (CRI)	80+									
AC Input Rating (VAC)	AC 100-277 v 50/60Hz									
Dimming (0-10v)	Optional									
PF	≥0.90									

ORDERING INFORMATION

MODEL	LUMEN EFFICACY		POWER		CCT
IK-MT24	L110	-	10	-	30
			0 - 10 W		30 - 3000K
			0 - 15 W		40 - 4000K
			0 - 20 W		50 - 5000K











