

Retrofit Down Lights



**ZENERGY**
The LED Revolution

The IKIO Retrofit Down Light Series comprises of wide beam angle options and advanced dimming capabilities which minimizes to 5% with widely available traditional dimmers. It can also be directly installed on 4-inch or 6-inch junction box

Features

- Replaces 40W to 100W existing cans
- UL listed / CUL listed
- Heat and impact resistant housing
- Low starting temperature -40o C
- 80+ CRI
- 110 Beam angle
- 100,000-hours of lifetime at L70
- Multi-volt (100 -277V) input
- 10-Year Manufacturer's Warranty

Powered by
 **IKIO**
LED LIGHTING



Internal Product Code	IK-XR06-L090-0010-XX-XX	IK-XRET-L090-0010-XX-XX	IK-XECO-L090-0010-XX-XX
Size (mm)	-		
Power Consumption (W)	10		
Lumen Output (Lm)	900 ± 5%		
Lumen Efficacy (Lm/W)	90 ± 5%		
CCT (K)	2700 ± 5%	3000 ± 5%	4000 ± 5%
Color Rendering Index (CRI)	80+		
AC Input Rating (vAC)	AC 100-277v 50/60Hz		
Dimming (0-10v)	Optional		
PF	≥ 0.90		

ORDERING INFORMATION

